Australian distributor:

Ultimate Dental Supply

MOORABBIN VIC 3189

Email: info@ultimatedental.com.au

Emergency: 13 11 26 POISONS 24/7

660a South Rd

Tel: 03 9532 1799

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Plastodur die hardner

Revision date: 19.01.2022 Page 1 of 11

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Plastodur die hardner

Product code:

26000

UFI: A833-J0H2-A00E-CW61

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Non-metal surface treatment products Restricted to professional users.

1.3. Details of the supplier of the safety data sheet

Company name: DFS-DIAMON GmbH

Street: Ländenstr. 1
Place: D-93339 Riedenburg
Telephone: +49(0)944291890
e-mail: info@dfs-diamon.de

e-mail: info@dis-diamon.c
Contact person: Armin Aunkofer

e-mail: armin.aunkofer@dfs-diamon.de

Internet: www.dfs-diamon.de

1.4. Emergency telephone 24 hour Emergency Contact: +49 (0) 700 24112112 (DFS)

<u>number:</u> +1 872 5888271

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3: H336

Full text of hazard statements: see SECTION 16.

2.2. Label elements

Regulation (EC) No 1272/2008

Hazard components for labelling

ethyl acetate

acetone; propan-2-one; propanone propan-2-ol; isopropyl alcohol; isopropanol

Signal word: Danger

Pictograms:





Hazard statements

H225 Highly flammable liquid and vapour.
 H319 Causes serious eye irritation.
 H336 May cause drowsiness or dizziness.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

according to Regulation (EC) No 1907/2006

Plastodur die hardner

Revision date: 19.01.2022 Page 2 of 11

smoking.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P233 Keep container tightly closed.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P403+P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of waste according to applicable legislation

Special labelling of certain mixtures

EUH066 Repeated exposure may cause skin dryness or cracking.

2.3. Other hazards

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) N			
141-78-6	ethyl acetate			30 - 40 %
	205-500-4	607-022-00-5		
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336 EUH066			
67-64-1	acetone; propan-2-one; propanone			30 - 40 %
	200-662-2	606-001-00-8	01-2119471330-49	
	Flam. Liq. 2, Eye Irrit. 2, STOT S			
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol			20 - < 25 %
	200-661-7	603-117-00-0	01-2119457558-25	
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336			
108-65-6	2-methoxy-1-methylethyl acetate			10 - < 15 %
	203-603-9	607-195-00-7	01-2119475791-29	
	Flam. Liq. 3; H226			

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

When in doubt or if symptoms are observed, get medical advice.

After inhalation

Provide fresh air. If breathing is irregular or stopped, administer artificial respiration. If experiencing respiratory symptoms: Get medical advice/attention.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Immediately remove any contaminated clothing, shoes or stockings. In case of skin reactions, consult a physician.

Do not wash with: Solvents/Thinner.

according to Regulation (EC) No 1907/2006

Plastodur die hardner

Revision date: 19.01.2022 Page 3 of 11

After contact with eyes

Rinse immediately carefully and thoroughly with eye-bath or water. In case of eye irritation consult an ophthalmologist. Remove contact lenses, if present and easy to do. Continue rinsing.

After ingestion

Observe risk of aspiration if vomiting occurs. If swallowed, rinse mouth with water (only if the person is conscious). Do NOT induce vomiting. Seek medical advice immediately.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Water mist, Carbon dioxide (CO2), alcohol resistant foam, Extinguishing powder.

Co-ordinate fire-fighting measures to the fire surroundings.

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

Highly flammable, Vapours can form explosive mixtures with air. Vapours are heavier than air.

In case of fire may be liberated: Pyrolysis products, toxic.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus. Full protection suit.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Do not breathe gas/vapour/aerosol. Avoid contact with skin, eyes and clothes. Evacuate area. Remove persons to safety.

For non-emergency personnel

Remove all sources of ignition. Provide adequate ventilation. Use personal protection equipment.

For emergency responders

Use personal protection equipment.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment

Stop leak if safe to do so.

For cleaning up

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

Clean floors and contaminated objects with: Water (with cleaning agent).

Other information

Do not wash with: Solvents/Thinner.

according to Regulation (EC) No 1907/2006

Plastodur die hardner

Revision date: 19.01.2022 Page 4 of 11

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Provide adequate ventilation. Do not breathe gas/vapour/aerosol. Avoid contact with skin, eyes and clothes. Evacuate area. Use personal protection equipment.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges. Vapours are heavier than air. Vapours can form explosive mixtures with air.

Advice on general occupational hygiene

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.

Further information on handling

Observe technical data sheet. Observe instructions for use.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Hints on joint storage

Do not store together with: Acid, alkali. Oxidising agent. Pyrophoric or self-heating substances.

Further information on storage conditions

storage temperature 15 - 30 °C

Keep away from heat. Protect from direct sunlight.

7.3. Specific end use(s)

Non-metal surface treatment products Restricted to professional users.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

CAS No	Substance	ppm	mg/m³	fib/cm³	Category	Origin
108-65-6	2-Methoxy-1-methylethylacetate	50	275		TWA (8 h)	
		100	550		STEL (15 min)	
67-64-1	Acetone	500	1210		TWA (8 h)	
141-78-6	Ethyl acetate	200	734		TWA (8 h)	
		400	1468		STEL (15 min)	
67-63-0	Isopropyl alcohol	200	-		TWA (8 h)	
		400	-		STEL (15 min)	

according to Regulation (EC) No 1907/2006

Plastodur die hardner

Revision date: 19.01.2022 Page 5 of 11

Biological limit values

CAS No	Substance	Parameter	Value	Test material	Sampling time
67-64-1	Acetone	Acetone	50 mg/L	Urine	End of shift
67-63-0	2-Propanol	Acetone	40 mg/L	_	End of shift at end of workweek

DNEL/DMEL values

CAS No	Substance				
DNEL type		Exposure route	Effect	Value	
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol				
Worker DNEL, long-term		dermal	systemic	888 mg/kg bw/day	
Worker DNEL, long-term		inhalation	systemic	500 mg/m³	

PNEC values

CAS No	Substance		
Environmental compartment V		Value	
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol		
Freshwater		140,9 mg/l	
Freshwater (i	intermittent releases)	140,9 mg/l	
Marine water		140,9 mg/l	
Marine sediment		552 mg/kg	
Micro-organisms in sewage treatment plants (STP)		2251 mg/l	
Soil		28 mg/kg	

8.2. Exposure controls









Appropriate engineering controls

Provide adequate ventilation as well as local exhaustion at critical locations.

Individual protection measures, such as personal protective equipment

Eye/face protection

Use eye protection according to EN 166. Tightly sealed safety glasses.

Hand protection

Wear suitable gloves tested to EN374.

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Skin protection

Wear suitable protective clothing.

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

Respiratory protection necessary at: exceeding exposure limit values.

Use only respiratory protection equipment with CE-symbol including four digit test number.

according to Regulation (EC) No 1907/2006

Plastodur die hardner

Revision date: 19.01.2022 Page 6 of 11

Thermal hazards

Flame-retardant protective clothing.

Environmental exposure controls

Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Liquid

Colour: colourless, clear
Odour: Solvent/Thinner.
Odour threshold: not determined

Changes in the physical state

Melting point/freezing point: not determined

Boiling point or initial boiling point and (Acetone) 56 °C

boiling range:

Flash point: (Acetone) -18 °C

Flammability

Solid/liquid: not applicable
Gas: not applicable

Explosive properties

Vapours can form explosive mixtures with air.

Lower explosion limits: 1,5 vol. % Upper explosion limits: 12,8 vol. %

Auto-ignition temperature: (2-methoxy-1-methylethyl acetate) 315 °C

Self-ignition temperature

Solid: not applicable
Gas: not applicable
Decomposition temperature: not determined
pH-Value: not determined
Viscosity / kinematic: not determined
Water solubility: not determined

Solubility in other solvents

not determined

Partition coefficient n-octanol/water: not determined

Vapour pressure: ((Acetone)) 246 hPa

(at 20 °C)

Density: 0,83 g/cm³
Relative vapour density: not determined
Particle characteristics: not applicable

9.2. Other information

Other safety characteristics

No information available.

SECTION 10: Stability and reactivity

10.1. Reactivity

Highly flammable,.

according to Regulation (EC) No 1907/2006

Plastodur die hardner

Revision date: 19.01.2022 Page 7 of 11

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Vapours can form explosive mixtures with air.

Exothermic reaction with: Strong acid. Strong alkali. Oxidising agent, strong.

10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Keep away from heat. Protect from direct sunlight.

10.5. Incompatible materials

Acid, alkali. Oxidising agent. Pyrophoric or self-heating substances.

10.6. Hazardous decomposition products

In case of fire may be liberated: Pyrolysis products, toxic.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Based on available data, the classification criteria are not met.

Irritation and corrosivity

Causes serious eye irritation.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness. (ethyl acetate; acetone; propan-2-one; propanone; propan-2-ol; isopropyl alcohol; isopropanol)

STOT-repeated exposure

Repeated exposure may cause skin dryness or cracking.

Aspiration hazard

Based on available data, the classification criteria are not met.

Information on likely routes of exposure

Eye contact, Skin contact, Inhalation, oral.

11.2. Information on other hazards

Endocrine disrupting properties

No information available.

SECTION 12: Ecological information

12.1. Toxicity

The product is not: Ecotoxic.

12.2. Persistence and degradability

The product has not been tested.

12.3. Bioaccumulative potential

The product has not been tested.

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

according to Regulation (EC) No 1907/2006

Plastodur die hardner

Revision date: 19.01.2022 Page 8 of 11

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII. The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

No information available.

12.7. Other adverse effects

No information available.

Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Dispose of waste according to applicable legislation.

Contaminated packaging

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number: UN 1263

14.2. UN proper shipping name: PAINT RELATED MATERIAL

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3



Classification code: F1

Special Provisions: 163 367 640D 650

Limited quantity: 5 L
Excepted quantity: E2
Transport category: 2
Hazard No: 33
Tunnel restriction code: D/E

Inland waterways transport (ADN)

14.1. UN number or ID number: UN 1263

14.2. UN proper shipping name: Paint related material

 14.3. Transport hazard class(es):
 3

 14.4. Packing group:
 II

 Hazard label:
 3



Classification code: F1

Special Provisions: 163 367 640D 650

Limited quantity: 5 L Excepted quantity: E2

according to Regulation (EC) No 1907/2006

Plastodur die hardner

Revision date: 19.01.2022 Page 9 of 11

Marine transport (IMDG)

14.1. UN number or ID number: UN 1263

14.2. UN proper shipping name: PAINT RELATED MATERIAL

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3



Marine pollutant:

Special Provisions: 163, 367
Limited quantity: 5 L

Excepted quantity: E2

EmS: F-E, S-E

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 1263

14.2. UN proper shipping name: PAINT RELATED MATERIAL

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3



Special Provisions: A3 A72 A192

Limited quantity Passenger: 1 L
Passenger LQ: Y341
Excepted quantity: E2

IATA-packing instructions - Passenger:353IATA-max. quantity - Passenger:5 LIATA-packing instructions - Cargo:364IATA-max. quantity - Cargo:60 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

Warning: flammable liquids. Vapours can form explosive mixtures with air.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 75

2010/75/EU (VOC): <= 100 %

Information according to 2012/18/EU P5c FLAMMABLE LIQUIDS

(SEVESO III):

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile

work protection guideline' (94/33/EC).

according to Regulation (EC) No 1907/2006

Plastodur die hardner

Revision date: 19.01.2022 Page 10 of 11

Water hazard class (D): 1 - slightly hazardous to water

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 1,2,4,5,6,7,8,9,10,11,12,13,14,15,16.

Abbreviations and acronyms

CLP: Classification, labelling and Packaging

REACH: Registration, Evaluation and Authorization of Chemicals

GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals

UN: United Nations

CAS: Chemical Abstracts Service
DNEL: Derived No Effect Level
DMEL: Derived Minimal Effect Level
PNEC: Predicted No Effect Concentration

ATE: Acute toxicity estimate LC50: Lethal concentration, 50%

LD50: Lethal dose, 50% LL50: Lethal loading, 50% EL50: Effect loading, 50%

EC50: Effective Concentration 50%

ErC50: Effective Concentration 50%, growth rate NOEC: No Observed Effect Concentration

BCF: Bio-concentration factor

PBT: persistent, bioaccumulative, toxic vPvB: very persistent, very bioaccumulative

ADR: Accord européen sur le transport des marchandises dangereuses par Route

(European Agreement concerning the International Carriage of Dangerous Goods by Road)

RID: Regulations concerning the international carriage of dangerous goods by rail

ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways (Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures)

IMDG: International Maritime Code for Dangerous Goods

EmS: Emergency Schedules MFAG: Medical First Aid Guide

IATA: International Air Transport Association ICAO: International Civil Aviation Organization

MARPOL: International Convention for the Prevention of Marine Pollution from Ships

IBC: Intermediate Bulk Container VOC: Volatile Organic Compounds SVHC: Substance of Very High Concern

For abbreviations and acronyms, see table at http://abbrev.esdscom.eu

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure			
Flam. Liq. 2; H225	On basis of test data			
Eye Irrit. 2; H319	Calculation method			
STOT SE 3; H336	Calculation method			

Relevant H and EUH statements (number and full text)

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H319	Causes serious eve irritation.

according to Regulation (EC) No 1907/2006

Plastodur die hardner

Revision date: 19.01.2022 Page 11 of 11

H336 May cause drowsiness or dizziness.

EUH066 Repeated exposure may cause skin dryness or cracking.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)