

Effective Date 18-Sep-2020

SAFETY DATA SHEET

Version 4

1. IDENTIFICATION

Product Identifier Product Name **PREMIUM SUPER-20 LIQUID** Other means of identification SDS# 035 UN/ID No UN1993 Product Code 0604, 0606, 0607, 0608, 0634, 0656 Recommended use of the chemical and restrictions on use Recommended Use Fabrication of dentures Details of the supplier of the safety data sheet Supplier Lang Dental Mfg. Co., Inc. Address 175 Messner Dr. Wheeling, IL 60090 USA +1-847-215-6622 Emergency telephone number Australia 13 11 26 Poisons Hotline 24hours/7 days) Australian Distributor **Ultimate Dental Supplies** 660A South Road Moorabbin Vic 3192 Tel: 03 9532 1799 Fax: 03 9555 9458 Info@ultimatedental.com.au www.ultimatedental.com.au

2. HAZARDS IDENTIFICATION

Catego	ory 2
Catego	ory 2
Catego	ory 1
Catego	ory 3

Signal word Danger Hazard statements H225

H315 Highly flammable liquid and vapor.

H317 Causes skin irritation.

H335 May cause an allergic skin reaction. May cause respiratory irritation.



Physical state Liquid

Odor Acrid

Precautionary Statements - Prevention

P210 Keep away from heat/sparks/open flames/ hot surfaces. No smoking. P233

Keep container tightly closed.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ventilating/lighting/equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P261 Avoid breathing dust/fume/gas/mist/vapors/spray.

P264 Wash hands thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P272 Contaminated work clothing should not be allowed out of the workplace. P280

Wear protective gloves/protective clothing/eye protection/face protection.

Precautionary Statements - Response

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. P312 Call a

POISON CENTER or doctor/physician if you feel unwell.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P362 Take off contaminated clothing and wash before use.

P370+P378 In case of fire: Use CO2, for extinction.

Precautionary Statements - Storage

P235 Keep cool. P403+P233 Store in a well-ventilated place. Keep container tightly closed.

Precautionary Statements - Disposal

P501 Dispose of contents/container in accordance with local regulation.

Chemical Name	CAS No	Weight - %	Trade Secret
Methyl Methacrylate	80-62-6	<100	*
Ethylene Glycol Dimethacrylate	97-90-5	<5	*

*Specific chemical weight has been withheld as a trade secret.

Hazardous component(s) for labeling Contains methyl methacrylate

3. COMPOSITION / INFORMATION ON INGREDIENTS

4. FIRST AID MEASURES

	First aid measures
Inhalation Eye	Remove victim to fresh air. Keep at rest in a position comfortable for breathing. Seek immediate medical attention.
	Rinse immediately with plenty of water, including under the eyelids, for at least 15 minutes. If irritation persists, call a
contact	physician immediately.
	If ingested, do not induce vomiting. Drink plenty of water or milk immediately. If vomiting, continue to offer water or
Ingestion	milk. Never give anything by mouth to an unconscious person. Call a physician or poison control center immediately
	and provide an estimate of when and how much material was ingested. Seek immediate medical attention.
	Wash with soap and water. If irritation, redness or swelling persists, call a physician immediately. Take off
	contaminated clothing and wash before reuse.
Skin Contact	
	Most important symptoms and effects, both acute and delayed
	Symptoms No information available.
Indication of any immediate	a modical attention and enocial treatment needed

 Indication of any immediate medical attention and special treatment needed

 Note to physicians
 T reat symptomatically.

5. FIRE-FIGHTING MEASURES

Extinguishing Media

Suitable: Chemical (alcohol-resistant) foam, dry chemical, or carbon dioxide,

Unsuitable: Water spray or water stream may not be effective.

Specific hazards arising from the chemical

For bulk size >1L - High temperatures, inhibitor depletion, accidental impurities, or exposure to radiation or oxidizers may cause spontaneous polymerizing reaction generating heat/pressure. Closed containers may rupture or explode during a runaway polymerization. This product is flammable liquid. Vapors of this product are heavier than air and may travel to a source of ignition and flash back to a leaking or open container. Vapor forms an explosive mixture with air.

Hazardous Combustion Products

Acrid smoke-fumes/carbon monoxide/carbon dioxide and perhaps other toxic vapors may be released during a fire involving this product. Special Fire

Fighting Procedures

Use a water spray or fog to reduce or direct vapors, and keep containers cool. Water may not be effective in actually extinguishing a fire involving this product. Do not enter fire area without proper protection. Fight fire from a safe location. Structural firefighters must wear SCBAs and full protective equipment. Heat/Impurities may cause pressure to build and/or rupture closed containers, spreading fire, increasing risk of burns/injuries.

Protective equipment and precautions for firefighters

Wear self-contained breathing apparatus for firefighting if necessary. Do not enter area without proper protection. Fight fire from safe distance/protected location. Heat /impurities may increase temperature/build pressure/rupture closed containers, spreading fire, increasing risk of burns/injuries. Use water spray to cool unopened containers. Pressure relief system may plug with solids creating risk of overpressure.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions	Before cleaning any spill or leak, individuals must wear personal protective equipment as required. Remove any contaminated clothing and wash thoroughly before reuse.
Environmental precautions	ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Prevent product from entering drains. Spillages or uncontrolled discharges into watercourses must be alerted to the appropriate regulatory body.
Methods and material for containmer	nt and clean-up
Method for containment	Prevent further leakage or spillage if safe to do so. Dike and contain spill with inert material. Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. DO NOT use combustible materials such as sawdust. May contaminate water supply.
Method for clean-up	Maximize ventilation (open doors and windows) and secure all sources of ignition. Place into appropriate closed container(s) for disposal in accordance with local, state and federal regulations. Wash all affected areas with plenty of warm water and soap.
	7. HANDLING AND STORAGE
Precautions for safe handling	
Advice on safe handling	Keep away from heat, sparks, and flame. Keep container closed after each use. Avoid contact with skin, eyes and clothing. Use good personal hygiene and housekeeping. After use, wash hands and exposed skin with soap and water. Do not eat, drink, or smoke while handling product. Keep away from heat, sparks, and flame. Keep container closed after each use. Ground and bond all containers when transferring. Observe precautions found on the label.
Conditions for safe storage, including	g any incompatibilities
Storage Conditions	Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks, flame and other sources of ignition. Protect from direct sunlight. Keep container closed to prevent water absorption and contamination. Methacrylate stored in bulk quantities must be kept in contact with air (oxygen). Keep at temperature not exceeding 30°C/86 °F.
Packaging materials	Keep in original container.
Incompatible materials	Strong oxidizing agents, strong reducing agents, free-radical generators, inert gases, oxygen scavengers.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure guidelines

Consideration should be given to the work procedures involved and the potential extent of

exposure as they may determine whether a higher level of protection is required. The following information

	is given as general guidance.		
Chemical Name	ACGIH TLV	OSHA PEL	NIOSH
Methyl Methacrylate 80-62-6	STEL: 100 ppm TWA: 50 ppm	TWA:100 ppm TWA: 410 mg/m ³	TWA:100 ppm TWA: 410 mg/m ³
	mental Industrial Hygienists / OSHA = Occupat L - Short Term Exposure Limit / TLV - Thresho		
Appropriate engineering controls Engineering controls	For bulk size: Use local explosior	n-proof ventilation that is adequate	e to keep employee exposure to
	airborne concentrations below e	• •	
ndividual protection measures, such a	s personal protective equipment		
Eye / face protection	US OSHA 29CFR SS1910.133, Ca	duct, safety glasses or goggles ma nadian standards or the Europear sin is available in case of exposur	Standard EN 166. Ensure that an
Skin and body protection	gloves for routine industrial use.	repeated skin contact will occur d If necessary, refer to US OSHA 29 rember states. Wear suitable prote	OCFR SS1910.138 or the appropriate
Respiratory protection	necessary, use only respiratory papelicable US state regulations,	or the appropriate standards of Ca	tances of use or handling. If A requirement in 29 CFR SS 1910.134 anada, its provinces, or the EC memb
General hygiene considerations	states. VENTILATION: Local exhi	aust at processing equipment. industrial hygiene and safety pract	tice. Wash thoroughly after
	handling. Food, beverages and to		rried, stored, or consumed where thi

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state Appearance	Liquid Liquid	Odor Odor threshold	Acrid Not determined
Color	Clear		
Property	Values	Remarks / Method	
рН	Not determined		
Melting point / Freezing point Boiling point / boiling range	Not determined 101°C/214° F		
Flash point	12°C/54°F		
Evaporation rate	Not determined		
Flammability (solid, gas) Flammability limits in air	n/a (liquid)		
Upper flammability limit	Not applicable		
Lower flammability limit	Not applicable		
Specific gravity	0.954	Water = 1	
Autoignition temperature Other information	421°C/790°F		
Density	0.954 g/mL		

Information on basic physical and chemical properties

10. STABILITY AND REACTIVITY

Reactivity Unstable/Reactive upon depletion of inhibitor.

<u>Chemical stability</u> Stable under recommended storage conditions. <u>Possibility of hazardous reactions</u> None under normal processing Hazardous polymerization Hazardous polymerization may occur.

Incompatible materials

Strong oxidizing agents, strong reducing agents, free-radical generators, inert gases, oxygen scavengers Material has strong solvent properties and can soften paint and rubber.

Hazardous decomposition products Carbon oxides

11. TOXICOLOGICAL INFORMATION

 Mixture Toxicity Inhalation Toxicity: 4,632 mg/L

 Component Toxicity No data available Routes of

 Exposure - No data available Target Organs - Eyes, Skin,

 Respiratory System Inhalation
 Harmful if inhaled.

 Eye contact
 Causes severe eye irritation.

 Skin contact
 Causes skin irritation. May be harmful in contact with skin.

 Ingestion
 May be harmful if swallowed.

Product Components Listed as Carcinogenic None

Ecotoxicity Chemical Name Algae / aquatic plants Fish Crustacea Toxicity to microorganisms Methv 170: 96 h 243-275: 96 h Pimephales promelas mg/L LC50 69: 48 h Daphnia magna mg/L Methacrylate Pseudokirchneriella subcapitata flow-through; FC50 80-62-6 mg/L EC50 125.5-190.7: 96 h Pimephales promelas mg/L LC50 static; 170-206: 96 h Lepomis macrochirus mg/L LC50 flow-through; 153.9-341.8: 96 h Lepomis macrochirus mg/L LC50 static; 326.4-426.9 96 h Poecilia reticulata mg/L LC50 static: >79: 96 h Oncorhynchus mykiss mg/L LC50 flowthrough; >79: 96 h Oncorhynchus mykiss mg/L LC50 static

12. ECOLOGICAL INFORMATION

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal of wastes

Follow all local and national government regulations in disposing material or contaminated packaging.

For U.S. - Dispose of in accordance with federal, state and local regulations. When discarded, it is considered a hazardous waste by the EPA under RCRA. The reportable quantity for methyl methacrylate is 1000 lb. (40 CFR Part 302). Add excess inhibitor before disposing.

Contaminated Packaging

Reuse of empty drums or containers is not recommended. Employees should be advised of the potential hazards due to residual material associated with empty containers. Dispose of all empty containers in accordance with local and national government regulations.

14. TRANSPORTATION INFORMATION

DOT

UN / ID No	UN1993
Proper shipping name	Flammable liquid, n.o.s. (Methyl Methacrylate monomer, stabilized /
	Ethylene Glycol Dimethacrylate solution)
Hazard Class	3
Packing Group	Ш
Reportable Quantity (RQ)	1000 lb. (methyl methacrylate)

IATA

UN / ID No	UN1993
Proper shipping name	Flammable liquid, n.o.s. (Methyl Methacrylate monomer, stabilized / Ethylene Glycol Dimethacrylate solution)
Hazard Class	3
Packing Group	I

IMDG

UN / ID No	UN1993
Proper shipping name	Flammable liquid, n.o.s. (Methyl Methacrylate monomer, stabilized /
	Ethylene Glycol Dimethacrylate solution)
Hazard Class	3
Packing Group	ll l

15. REGULATORY INFORMATION

International Inver	ntories	
Methyl methacryla	te 80-62-6	
TSCA	Listed	United States Toxic Substances Control Act, Section 8(b) Inventory
DSL	Listed	Canadian Domestic Substances List
EINECS	Listed	European Inventory of Existing Chemical Substances

EU Regulations EC No. 1272/2008 (CLP) Classification, Labeling, Packaging Medical Devices Directive 93/42/EEC - Class I Medical Devices

US Federal Regulations SARA 302 - Extremely hazardous substance - not listed SARA 311/312 - Hazard categories - listed Methyl methacrylate 80-62-6 SARA 313 - Methyl Methacrylate 80-62-6

US State Regulations California Proposition 65 - Warning. This product contains the following chemicals which are listed by the State of California as carcinogenic or a reproductive toxin: None

US State Right-to-Know Regulations Not established

16. OTHER INFORMATION

NFPA	Health Hazards	Flammability	Instability
	2	3	2
HMIS	Health Hazards	Flammability	Physical Hazards
	2	3	2

Effective Date 18-Sept-2020 Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as guidance for safe handling, use, processing, storage, transportation, disposal and release. It is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet